



WE KEEP YOU CUTTING®

2009 PRODUCT SPECIFICATIONS

PRODUCT NAME	XDZ 272H		XDZ 266H		XDZ 266M		XDZ 260H				XDZ 260M			XDZ 252H		XDZ 252M
MODEL NUMBER	992168*	992160*	992170	992167*	992165*	992166*	992164*	992159	992154	992156	992175*	992162*	992152*	992163*	992150	992161*
WARRANTY	2 Year		2 Year		2 Year		2 Year				2 Year			2 Year		2 Year
ENGINE	Kawasaki®	Daihatsu®	Kohler® Command	Kawasaki®	Kawasaki®	Kawasaki®			Kohler® Command	Daihatsu®	Kawasaki®			Kawasaki®	Kohler® Command	Kawasaki®
HORSEPOWER	31	31LC	30	31	31	31	27	26LC	27	27LC	31	27	26LC	27		27
DRIVE SYSTEM	Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic				Hydrostatic			Hydrostatic		Hydrostatic
FUEL CAPACITY GALLONS (LITERS)	13 gallon (49L)		13 gallon (49L)		13 gallon (49L)		13 gallon (49L)				13 gallon (49L)			13 gallon (49L)		13 gallon (49L)
GROUND SPEED (Appx. Mph) (Forward/Rev)	13 mph/6 mph		13 mph/6 mph		13 mph/6 mph		13 mph/6 mph				13 mph/6 mph			13 mph/6 mph		13 mph/6 mph
STARTER	Electric		Electric		Electric		Electric				Electric			Electric		Electric
DECK																
DECK MATERIAL	7 ga		7 ga		7 ga		7 ga				7 ga			7 ga		7 ga
DECK CONSTRUCTION	Welded		Welded		Welded		Welded				Welded			Welded		Welded
NUMBER OF SPINDLES	3		3		3		3				3			3		3
BLADE TIP SPEED (FPM)	18,000		18,000		18,000		18,000				18,000			18,000		18,000
SPINDLE MATERIAL	Ductile Cast Iron		Ductile Cast Iron		Ductile Cast Iron		Ductile Cast Iron				Ductile Cast Iron			Ductile Cast Iron		Ductile Cast Iron
SPINDLE SHAFT	1" Dia. High Strength Steel		1" Dia. High Strength Steel		1" Dia. High Strength Steel		1" Dia. High Strength Steel				1" Dia. High Strength Steel			1" Dia. High Strength Steel		1" Dia. High Strength Steel
SPINDLE BEARINGS	Ball Bearing		Ball Bearing		Ball Bearing		Ball Bearing				Ball Bearing			Ball Bearing		Ball Bearing
DECK DRIVE	Belt		Belt		Belt		Belt				Belt			Belt		Belt
DECK ENGAGEMENT	Ogura® GT 3.5 Electric Clutch		Ogura® GT 3.5 Electric Clutch		Ogura® GT 3.5 Electric Clutch		Ogura® GT 3.5 Electric Clutch				Ogura® GT 3.5 Electric Clutch			Ogura® GT 3.5 Electric Clutch		Ogura® GT 3.5 Electric Clutch
DECK LIFT SYSTEM	Hydraulic		Hydraulic		Manual		Hydraulic				Manual			Hydraulic		Manual
CUTTING WIDTH	72"		66"		66"		60"				60"			52"		52"
CUTTING HEIGHTS	1"-5"		1"-5"		1"-5"		1"-5"				1"-5"			1"-5"		1"-5"
CUTTING POSITIONS	17 Cutting Positions in .25" increments		17 Cutting Positions in .25" increments		9 Cutting Positions in .50" increments		17 Cutting Positions in .25" increments				9 Cutting Positions in .50" increments			17 Cutting Positions in .25" increments		9 Cutting Positions in .50" increments
WHEELS																
FRONT AXLE	Pivoting/Locking		Pivoting/Locking		Pivoting/Locking		Pivoting/Locking				Pivoting/Locking			Pivoting/Locking		Pivoting/Locking
FRONT	Ribbed 15 x 6-6		Ribbed 15 x 6-6		Ribbed 15 x 6-6		Ribbed 15 x 6-6				Ribbed 15 x 6-6			Ribbed 15 x 6-6		Ribbed 15 x 6-6
REAR	Turf 24 x 11.5-12		Turf 24 x 11.5-12		Turf 24 x 11.5-12		Turf 24 x 11.5-12				Turf 24 x 11.5-12			Turf 24 x 11.5-12		Turf 24 x 11.5-12
FEATURES																
SAFETY	ANSI Compliant		ANSI Compliant		ANSI Compliant		ANSI Compliant				ANSI Compliant			ANSI Compliant		ANSI Compliant
HOOD	Standard		Standard		Standard		Standard				Standard			Standard		Standard
HEADLIGHTS	Optional		Optional		Optional		Optional				Optional			Optional		Optional
SEAT	High Back w/ Full Suspension		High Back w/ Full Suspension		High Back w/ Full Suspension		High Back w/ Full Suspension				High Back w/ Full Suspension			High Back w/ Full Suspension		High Back w/ Full Suspension
HOUR METER	Standard		Standard		Standard		Standard				Standard			Standard		Standard
MACHINE DIMENSION																
WEIGHT (LBS)	1260	1550	1232	1217	1212	1175	1170	1190	1175	1170	1160	1170	1145	1150	1145	1145
LENGTH (INCHES)	82"	83.5"	82"		82"	82"				83.5"	82"			82"		82"
WIDTH (INCHES)	75" w/o Chute		70" w/o Chute		70" w/o Chute		63" w/o Chute				63" w/o Chute			55.5" w/o Chute		55.5" w/o Chute
HEIGHT (INCHES)	50"		50"		50"		50"				50"			50"		50"
ACCESSORIES/ATTACHMENTS	3 Bucket Powered Bagger Kit (except XDZ 260H/992156), Hopper Style Bagger Kit (except XDZ 272H/992160), Mulching Kit, Striper Kit, Discharge Cover, Trailer Hitch Kit, Head Light Kit, Foldable Rops, Bar Style Tire Kit, Electric Deck Lift Kit (except XDZ 252H, XDZ 260H, XDZ 266H, XDZ 272H), Snow Blade, Snow Head, Quick Hitch Kit, Debris Blower, Rotary Sweeper, Solid Front Caster Tire Kit, Turfglider Sport, Gravely Seat Cover, Liftmaster, Wheel Covers, FlexTend™ Shoulder Support System															

*This equipment meets 2009 California EVP emission regulations.

Available Feb-May 09 only

Available Starting in May 09

PRODUCT NAME	XDZ 266H LP	XDZ 260H LP	XDZ 152M	XDZ 148M	XDZ 144M	160iM XDZ	152iM XDZ	148iM XDZ	160iM XDZ	152iM XDZ	148iM XDZ
MODEL NUMBER	992183*	992182*	991028*	991027*	991026*	991067*	991061	991060	991064	991063	991062
WARRANTY	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year
ENGINE	Generac®	Generac®	Kawasaki®	Kawasaki®	Kawasaki®	Kawasaki® FH	Kawasaki® FH	Kawasaki® FH	Kawasaki® FX	Kawasaki® FX	Kawasaki® FX
HORSEPOWER	28	28	23	21	21	25	23	23	26	24	24
DRIVE SYSTEM	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	ZT3400 Transaxles	ZT3400 Transaxles	ZT3400 Transaxles	ZT3400 Transaxles	ZT3400 Transaxles	ZT3400 Transaxles
FUEL CAPACITY GALLONS (LITERS)	Twin 33.5 lb LP Tanks (Not Included)	Twin 33.5 lb LP Tanks (Not Included)	10 gallon (37.8L)	10 gallon (37.8L)	10 gallon (37.8L)	10 gallon (37.8L)	10 gallon (37.8L)	10 gallon (37.8L)	10 gallon (37.8L)	10 gallon (37.8L)	10 gallon (37.8L)
GROUND SPEED (Appx. Mph) (Forward/Rev)	13 mph/6 mph	13 mph/6 mph	10 mph/4.5 mph	10 mph/4.5 mph	10 mph/4.5 mph	10 mph/4.5 mph	10 mph/4.5 mph	10 mph/4.5 mph	10 mph/4.5 mph	10 mph/4.5 mph	10 mph/4.5 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
DECK											
DECK MATERIAL	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3	3	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000
SPINDLE MATERIAL	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron
SPINDLE SHAFT	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT 3.5 Electric Clutch	Ogura® GT 3.5 Electric Clutch	Ogura® GT 3.5 Electric Clutch	Ogura® GT 3.5 Electric Clutch	Ogura® GT 3.5 Electric Clutch	Ogura® GT 2.5 Electric Clutch	Ogura® GT 2.5 Electric Clutch	Ogura® GT 2.5 Electric Clutch	Ogura® GT 2.5 Electric Clutch	Ogura® GT 2.5 Electric Clutch	Ogura® GT 2.5 Electric Clutch
DECK LIFT SYSTEM	Hydraulic	Hydraulic	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual
CUTTING WIDTH	66"	60"	52"	48"	44"	60"	52"	48"	60"	52"	48"
CUTTING HEIGHTS	1"-5"	1"-5"	1"-5"	1"-5"	1"-5"	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"
CUTTING POSITIONS	17 Cutting Positions in .25" increments	17 Cutting Positions in .25" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments
WHEELS											
FRONT AXLE	Pivoting/Locking	Pivoting/Locking	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
FRONT	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6	Ribbed 15 x 6-6
REAR	Turf 24 x 11.5-12	Turf 24 x 11.5-12	Turf 23 x 10-12	Turf 23 x 10-12	Turf 23 x 10-12	Turf 23 x 10-12	Turf 23 x 10-12	Turf 23 x 10-12	Turf 23 x 10-12	Turf 23 x 10-12	Turf 23 x 10-12
FEATURES											
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant
HOOD	Standard	Standard	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
HEADLIGHTS	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
SEAT	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension	High Back w/ Full Suspension
HOOR METER	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
MACHINE DIMENSION											
WEIGHT (LBS)	TBD	TBD	986	976	971	961	961	951	961	961	946
LENGTH (INCHES)	82"	82"	72.5"	72.5"	72.5"	75"	72.5"	72.5"	75"	72.5"	72.5"
WIDTH (INCHES)	TBD	TBD	55.5" w/o Chute	50" w/o Chute	46.8" w/o Chute	63" w/o Chute	55.5" w/o Chute	50" w/o Chute	63" w/o Chute	55.5" w/o Chute	50" w/o Chute
HEIGHT (INCHES)	50"	50"	47"	47"	47"	47"	47"	47"	47"	47"	47"
ACCESSORIES/ATTACHMENTS											
Mulching Kit, Striper Kit, Discharge Cover, Trailer Hitch Kit, Head Light Kit, Foldable Rops, Bar Style Tire Kit, Quick Hitch Kit, Solid Front Caster Tire Kit, Turf Rider Sport, Gravely Seat Cover, Liftmaster, Suspension Seat Kit, FlexTend™ Shoulder Support System, Wheel Covers			Powered Bagger Kit, Mulching Kit, Striper Kit, Double Blade Kit (except XDZ 152M), Discharge Cover, Trailer Hitch Kit, Head Light Kit, Foldable Rops, Bar Style Tire Kit (except XDZ 144M), Electric Deck Lift Kit, Wheel Covers, FlexTend™ Shoulder Support, Solid Front Caster Tire Kit, Step Kit (except 144M)			Powered Bagger Kit, Mulching Kit, Striper Kit, Double Blade Kit (except 160iM, 152iM), Discharge Cover, Trailer Hitch Kit, Head Light Kit, Foldable Rops, Bar Style Tire Kit (except 160iM), Wheel Covers, FlexTend™ Shoulder Support			Powered Bagger Kit, Mulching Kit, Striper Kit, Double Blade Kit (except 160iM, 152iM), Discharge Cover, Trailer Hitch Kit, Head Light Kit, Foldable Rops, Bar Style Tire Kit (except 160iM), Wheel Covers, FlexTend™ Shoulder Support		

*This equipment meets 2009 California EVP emission regulations.

PRODUCT NAME	Compact 48Z	Compact 44Z	Compact 34Z	Pro Stance™ 2352FX	Pro Stance™ 2352FL	Pro Stance™ 1952FX	Pro Stance™ 1948FL	Pro Stance™ 1934FX	RAPID XZ		PM 320HD	
MODEL NUMBER	991059	991058	991022	994102	994103	994101	994100	994104	990100	990102	990023*	990021
WARRANTY	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year		2 Year	
ENGINE	Kawasaki®	Kawasaki®	Kawasaki®	Kawasaki®	Kawasaki®	Kawasaki® Kai	Kawasaki® Kai	Kawasaki® Kai	Kohler® Command		Kawasaki®	Kohler® Command
HORSEPOWER	19	19	17	23	23	19	19	19	27	30	27	
DRIVE SYSTEM	ZT2800 Transaxles	ZT2800 Transaxles	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic		Hydrostatic	
FUEL CAPACITY GALLONS (LITERS)	10 gallon (37.8L)	10 gallon (37.8L)	7 gallon (26.5L)	6 gallon (22.7L)	6 gallon (22.7L)	6 gallon (22.7L)	6 gallon (22.7L)	5 gallon (18.9L)	7.5 gallon (28.4L)		7.5 gallon (28.4L)	
GROUND SPEED (Appx. Mph) (Forward/Rev)	8 mph/4 mph	8 mph/4 mph	9 mph/4.5 mph	9 mph/4.5 mph	9 mph/4.5 mph	9 mph/4.5 mph	9 mph/4.5 mph	9 mph/4.5 mph	13 mph/6 mph		9.5 mph/5 mph	
STARTER	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric		Electric	
DECK												
DECK MATERIAL	10 ga	10 ga	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga		7 ga	
DECK CONSTRUCTION	Welded	Welded	Welded	Welded (fixed)	Welded (float)	Welded (fixed)	Welded (float)	Welded (fixed)	Welded		Welded	
NUMBER OF SPINDLES	3	3	2	3	3	3	3	2	3		3	
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000		18,000	
SPINDLE MATERIAL	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Ductile Cast Iron		Ductile Cast Iron	
SPINDLE SHAFT	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Steel	1" Steel	1" Steel	1" Steel	1" Steel	1" Dia. High Strength Steel		1" Dia. High Strength Steel	
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Sealed Ball Bearing	Sealed Ball Bearing	Sealed Ball Bearing	Sealed Ball Bearing	Sealed Ball Bearing	Ball Bearing		Ball Bearing	
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt		Belt	
DECK ENGAGEMENT	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Warner® 125 ft-lb Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Warner® 200 ft-lb Electric Clutch		Ogura® GT 3.5 Electric Clutch	
DECK LIFT SYSTEM	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Hydraulic		Hydraulic	
CUTTING WIDTH	48"	44"	34"	52"	52"	52"	48"	34"	60"	72"	60"	
CUTTING HEIGHTS	1"-5"	1"-5"	1"-5"	1.5"-5"	1.5"-5"	1.5"-5"	1.5"-5"	1.5"-5"	1"-5"		1"-5"	
CUTTING POSITIONS	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	9 Cutting Positions in .50" increments	15 Cutting Positions in .25" increments	15 Cutting Positions in .25" increments	15 Cutting Positions in .25" increments	15 Cutting Positions in .25" increments	15 Cutting Positions in .25" increments	Infinite		Infinite	
WHEELS												
FRONT AXLE	Fixed	Fixed	Fixed	Rigid	Rigid	Rigid	Rigid	Rigid	Turf 24 x 11.5-12**		Turf 24 x 11.5-12**	
FRONT	13 x 5-6	13 x 5-6	13 x 5-6	11 x 4-5	13 x 5-6	11 x 4-5	13 x 5-6	11 x 4-5	9 x 3.5-4		9 x 3.5-4	
REAR	20 x 10-10	20 x 10-10	21 x 7-10	18 x 8.5-8	20 x 10-8	18 x 8.5-8	20 x 10-8	18 x 6.5-8	13 x 5.25-4		16 x 6.5-8	
FEATURES												
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant		ANSI Compliant	
HOOD	N/A	N/A	N/A	No	No	No	No	No	Yes		No	
HEADLIGHTS	Optional	Optional	Optional	No	No	No	No	No	No		No	
SEAT	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs	N/A	N/A	N/A	N/A	N/A	High Back w/ Full Suspension		High Back w/ Full Suspension	
HOOR METER	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard		Standard	
MACHINE DIMENSION												
WEIGHT (LBS)	805	800	725	860	930	860	900	830	1650		925 w/o Deck	
LENGTH (INCHES)	71.5"	71.5"	71.5"	58"	80"	58"	80"	58.5"	75.5" w/o Deck		70" w/o Deck	
WIDTH (INCHES)	50" w/ Chute	46.8" w/ Chute	35.4"	64" Chute down 53" Chute up	64" Chute down 53" Chute up	64" Chute down 53" Chute up	60" Chute down 49" Chute up	47" Chute down 35" Chute up	48" w/o Deck		50.3" w/o Deck	
HEIGHT (INCHES)	42"	42"	42"	47.5"	48"	47.5"	47"	47"	45.5" top of seat back		50.8"	
ACCESSORIES/ATTACHMENTS												
	Bagger Kit, Mulching Kit, Striper Kit (except 34Z), Discharge Cover (except 34Z), Head Light Kit, Suspension Seat Kit, Wheel Covers, FlexTend™ Shoulder Support			Mulching Kit, Wheel Covers				Hopper Style Bagger Kit, Mulching Kit, Striper Kit, Discharge Cover, Trailer Hitch Kit, Head Light Kit, Foldable Rops, Bar Style Tire Kit, Snow Blade, Snow Head, Suspension Seat Kit, Rotary Sweeper Broom		Powered Bagger Kit, Mulching Kit, Striper Kit, Discharge Cover, Suspension Seat Kit, Wheel Covers		

*This equipment meets 2009 California EVP emission regulations.

**Drive Tires

PRODUCT NAME	RAPID M	RAPID U	RAPID E
MODEL NUMBER	985403	985402 (while supplies last)	985400
WARRANTY	2 Year	2 Year	2 Year
ENGINE	Briggs & Stratton®	Briggs & Stratton®	Briggs & Stratton®
HORSEPOWER	13	13	20
DRIVE SYSTEM	Hydrostatic	Hydrostatic	Hydrostatic
FUEL CAPACITY GALLONS (LITERS)	1.6 gallon (6.05L)	2.1 gallon (7.94L)	3.8 gallon (14.38L)
GROUND SPEED (Appx. Mph) (Forward/Rev)	3.4 mph/0.4 mph	3.7 mph/2.5 mph	5.0 mph/2.0 mph
STARTER	Recoil	Recoil/Electric	Recoil/Electric
DECK			
DECK MATERIAL	N/A	N/A	N/A
DECK CONSTRUCTION	N/A	N/A	N/A
NUMBER OF SPINDLES	N/A	N/A	N/A
BLADE TIP SPEED (FPM)	N/A	N/A	N/A
SPINDLE MATERIAL	N/A	N/A	N/A
SPINDLE SHAFT	N/A	N/A	N/A
SPINDLE BEARINGS	N/A	N/A	N/A
DECK DRIVE	N/A	N/A	N/A
DECK ENGAGEMENT	N/A	N/A	N/A
DECK LIFT SYSTEM	N/A	N/A	N/A
CUTTING WIDTH	N/A	N/A	N/A
CUTTING HEIGHTS	N/A	N/A	N/A
CUTTING POSITIONS	N/A	N/A	N/A
WHEELS			
FRONT AXLE	N/A	N/A	N/A
FRONT	N/A	N/A	N/A
REAR	18 x 7-8 Turf	20 x 8-10 Turf	23 x 8.5-12 Turf
FEATURES			
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant
HOOD	No	No	No
HEADLIGHTS	No	No	No
SEAT	No	No	No
HOOR METER	No	No	No
MACHINE DIMENSION			
WEIGHT (LBS)	340	349	520
LENGTH (INCHES)	70.5"	65.7"	70"
WIDTH (INCHES)	32.2"	34.2"	34"
HEIGHT (INCHES)	46.5"	31.5"-41.3"	34.3"
ATTACHMENTS			
SNOW BLOWER*	Available**	N/A	N/A
SNOW BLADE*	Available**	N/A	N/A
BRUSH*	Available**	N/A	N/A
30" DECK*	Available**	N/A	N/A
40" DECK*	Available**	N/A	N/A
CAR PUSHER	Available	N/A	N/A
RAPID SNOW BLOWER*	N/A	Available	Available
RAPID BLADE*	N/A	Available	Available
WEIDEMAN BRUSH	N/A	Available	Available

PRODUCT NAME	GR 1548FX	GR 1336FX	GR 1332FX	HR 1952FX	HR 1948FX	HR 1536FX
MODEL NUMBER	988145	988144	988143	988142	988141	988140
WARRANTY	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year
ENGINE	Kawasaki® Kai	Kawasaki® Kai	Kawasaki® Kai	Kawasaki® Kai	Kawasaki® Kai	Kawasaki® Kai
HORSEPOWER	15	13	13	19	19	15
DRIVE SYSTEM	5-Speed Peer-less Gear Drive	5-Speed Peer-less Gear Drive	5-Speed Peer-less Gear Drive	Pumps and Motors	Pumps and Motors	Pumps and Motors
FUEL CAPACITY GALLONS (LITERS)	6.6 gallon (25.1L)	6.6 gallon (25.1L)	6.6 gallon (25.1L)	6.6 gallon (25.1L)	6.6 gallon (25.1L)	6.6 gallon (25.1L)
GROUND SPEED (Appx. Mph) (Forward/Rev)	5.4 mph/Reverse Assist	5.4 mph/Reverse Assist	5.4 mph/Reverse Assist	7 mph/3 mph	7 mph/3 mph	7 mph/3 mph
STARTER	Recoil	Recoil	Recoil	Electric	Electric	Recoil
CYLINDERS	2	2	2	2	2	2
PARKING BRAKE SYSTEM	6" Drum	6" Drum	6" Drum	Paddle/Hand	Paddle/Hand	Paddle/Hand
DECK						
DECK MATERIAL	7 ga	7 ga	7 ga	7 ga	7 ga	7 ga
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	2	2	3	3	2
BLADE TIP SPEED (FPM)	16,596	18,152	16,614	18,246	16,496	18,261
SPINDLE MATERIAL	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
SPINDLE SHAFT	1" Steel	1" Steel	1" Steel	1" Steel	1" Steel	1" Steel
SPINDLE BEARINGS	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch
DECK LIFT SYSTEM	Manual	Manual	Manual	Manual	Manual	Manual
CUTTING WIDTH	48"	36"	32"	52"	48"	36"
CUTTING HEIGHTS	1.5"-4"	1.5"-4"	1.5"-4"	1.5"-5"	1.5"-5"	1.5"-5"
CUTTING POSITIONS	11 Cutting Positions in .25" increments	11 Cutting Positions in .25" increments	11 Cutting Positions in .25" increments	11 Cutting Positions in .25" increments	11 Cutting Positions in .25" increments	11 Cutting Positions in .25" increments
BLADE LENGTHS	16.5"	18"	16.5"	18"	16.5"	18"
DISCHARGE DIRECTION	Side	Side	Side	Side	Side	Side
WHEELS						
FRONT AXLE	Swivel Casters	Swivel Casters	Swivel Casters	Swivel Casters	Swivel Casters	Swivel Casters
FRONT	9 x 3.5 Solid	9 x 3.5 Solid	9 x 3.5 Solid	9 x 3.5 Solid	9 x 3.5 Solid	9 x 3.5 Solid
REAR	13 x 6.5	13 x 6.5	13 x 5	16 x 6.5	16 x 6.5	16 x 6.5
MACHINE DIMENSION						
WEIGHT (LBS)	548	481	478	667	647	547
LENGTH (INCHES)	70.9"	75.6"	73.9"	66"	69"	72"
WIDTH (INCHES)	60" w/ Chute	48" w/ Chute	45" w/ Chute	64" w/ Chute	60" w/ Chute	48" w/ Chute
HEIGHT (INCHES)	41.9"	41.9"	41.9"	43"	43"	43"
ACCESSORIES/ATTACHMENTS	Mulching Kit, Sulky, Hour Meter					

*Other Accessories Required for Attachment

** Requires Additional Kits To Mount

PRODUCT NAME	Pro Vac*	SuperStriper	String Trimmer	Power Brush	ZT 2760 HD	ZT 2560 HD	ZT 2552 HD	ZT 2552 HD	ZT 2348 HD	ZT 2344 HD
MODEL NUMBER		995408	946151	926503	991057	991055	991066	991054	991053	991052
WARRANTY	2 Year	Consumer Warranty	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year
ENGINE	Kohler® Command	Honda® GCV	Briggs & Stratton® 625 Series Quantum	All-Season	Kohler® Courage Pro V-Twin	Kohler® Courage V-Twin	Kohler® Courage V-Twin	Kohler® Courage Pro V-Twin	Kohler® Courage V-Twin	Kohler® Courage V-Twin
ENGINE RATING	18	160 cc	6.25	9	27	25	25	25	23	23
DRIVE SYSTEM	N/A	Push	Push	Disc-O-Matic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
FUEL CAPACITY GALLONS (LITERS)	6 gallon (23L)	0.37 gallon (1.4L)	0.4 gallon (1.5L)	4qt (3.8L)	7 gallon (26.5L)	7 gallon (26.5L)	7 gallon (26.5L)	7 gallon (26.5L)	7 gallon (26.5L)	7 gallon (26.5L)
GROUND SPEED (Appx. Mph) (Forward/Rev)	N/A	N/A	N/A	2.9 mph/1.4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
STARTER	Electric	Recoil	Recoil	Recoil	Electric	Electric	Electric	Electric	Electric	Electric
DECK										
DECK MATERIAL	14 ga	Aluminum	14 ga	N/A	10 ga	10 ga	10 ga	10 ga	10 ga	10 ga
DECK CONSTRUCTION	N/A	Welded	Stamped	N/A	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	N/A	N/A	1	N/A	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	N/A	18,000	N/A	N/A	18,000	18,000	18,000	18,000	18,000	18,000
SPINDLE MATERIAL	N/A	Steel	N/A	N/A	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron	Ductile Cast Iron
SPINDLE SHAFT	N/A	7/8"	N/A	N/A	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel	1" Dia. High Strength Steel
SPINDLE BEARINGS	N/A	N/A	N/A	N/A	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	N/A	Direct	Belt	N/A	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	N/A	N/A	Manual	N/A	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch	Ogura® GT 1A Electric Clutch
DECK LIFT SYSTEM	N/A	Manual	N/A	N/A	Manual	Manual	Manual	Manual	Manual	Manual
CUTTING WIDTH	N/A	21"	22"	N/A	60"	60"	52"	52"	48"	44"
CUTTING HEIGHTS	N/A	1"-4"	1.25"-4.25"	N/A	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"
CUTTING POSITIONS	N/A	8	4	N/A	9	9	9	9	9	9
WHEELS										
FRONT AXLE	No	Yes	No	No	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
FRONT	No	4" Roller	N/A	Caster	13 x 5-6	13 x 5-6	13 x 5-6	13 x 5-6	13 x 5-6	13 x 5-6
REAR	18.5	4" Roller	14	16 x 6.5	20 x 10-10	20 x 10-10	20 x 10-10	20 x 10-10	20 x 10-10	20 x 10-10
FEATURES										
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant
HOOD	No	No	No	N/A	N/A	N/A	N/A	N/A	N/A	N/A
HEADLIGHTS	No	No	No	Yes	Optional	Optional	Optional	Optional	Optional	Optional
SEAT	No	No	No	N/A	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs
HOOR METER	No	No	No	N/A	Standard	Standard	Standard	Standard	Standard	Standard
MACHINE DIMENSION										
WEIGHT (LBS)	1540	60	83	319	830	810	810	810	805	805
LENGTH (INCHES)	132"	56"	58"	76.5"	74.5"	74.5"	74.5"	74.5"	71.5"	71.5"
WIDTH (INCHES)	61"	23"	22"	44"	63" w/o Chute	55.5" w/o Chute	55.5" w/o Chute	55.5" w/o Chute	50" w/o Chute	50" w/o Chute
HEIGHT (INCHES)	73"	41"	41"	43"	42"	42"	42"	42"	42"	42"
ACCESSORIES/ATTACHMENTS										
			Engine Shield Kit, String Trimmer Line	Electric Start	Powered Bagger Kit, Mulching Kit, Striper Kit, Discharge Cover, Head Light Kit, Roller, Aerator, Dethatcher, Sprayer, Wheel Covers, Trailer Hitch Kit, FlexTend™ Shoulder Support System					

*Available through Gravelly Turf Dealers. To locate a dealer near you, call 888-927-4367.

PRODUCT NAME	ZT 2554XL	ZT 2548XL	ZT 2042XL		ZT 1734XL	ZT 2550	ZT 2350	ZT 2250	ZT 2040	ZT 1734	ZT 34
MODEL NUMBER	915138	915136	915110	915134	915108	915106	915132	915104	915102	915100	915130
WARRANTY	2 Year	2 Year	2 Year		2 Year	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year
ENGINE	Kohler® Courage V-Twin	Kohler® Courage V-Twin	Kohler® Courage Single	Kohler® Courage V-Twin	Kohler® Courage Single	Kohler® Courage V-Twin	Kohler® Courage V-Twin	Kohler® Courage Single	Kohler® Courage Single	Kohler® Courage Single	Briggs & Stratton® I/C
HORSEPOWER	25	25	20		17	25	23	22	20	17	344cc
DRIVE SYSTEM	ZT2800 Transaxles	ZT2800 Transaxles	ZT2800 Transaxles	EZT Transaxles w/ 1" axles	EZT Transaxles w/ 1" axles	EZT Transaxles w/ 1" axles	EZT Transaxles w/ 1" axles	EZT Transaxles w/ 1" axles	EZT Transaxles w/ 1" axles	EZT Transaxles w/ 1" axles	EZT Transaxles w/ 1" axles
FUEL CAPACITY GALLONS (LITERS)	4.5 gallon (17L)	4.5 gallon (17L)	4.5 gallon (17L)	3.25 gallon (12.3L)	3.25 gallon (12.3L)	3.25 gallon (12.3L)	3.25 gallon (12.3L)	3.25 gallon (12.3L)	3.25 gallon (12.3L)	3.25 gallon (12.3L)	2.5 gallon (9.5L)
GROUND SPEED (Appx. Mph) (Forward/Rev)	7 mph/3 mph	7 mph/3 mph	7 mph/3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
DECK											
DECK MATERIAL	10 ga w/ Doubler Plate	10 ga w/ Doubler Plate	10 ga w/ Doubler Plate	12 ga w/ Doubler Plate	12 ga w/ Doubler Plate	12 ga w/ Doubler Plate	12 ga w/ Doubler Plate	12 ga w/ Doubler Plate	12 ga w/ Doubler Plate	12 ga w/ Doubler Plate	12 ga
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped
NUMBER OF SPINDLES	3	3	3	2	3	3	3	3	3	2	2
BLADE TIP SPEED (FPM)	16,950	16,800	17,000	16,600	16,650	16,600	16,600	16,600	15,000	17,100	17,100
SPINDLE MATERIAL	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Steel
SPINDLE SHAFT	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel	1" Dia. Steel
SPINDLE BEARINGS	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Soft Touch Electric
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	54"	48"	42"	34"	50"	50"	50"	50"	40"	34"	34"
CUTTING HEIGHTS	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1"-4"
CUTTING POSITIONS	7	7	7	8	8	8	8	8	8	8	8
WHEELS											
FRONT AXLE	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
FRONT	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4	11 x 4
REAR	20 x 10	20 x 10	20 x 8	18 x 6.5	18 x 9.5	18 x 9.5	18 x 9.5	18 x 9.5	18 x 8.5	18 x 6.5	18 x 6.5
FEATURES											
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant
HOOD	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional	Optional	Optional	Standard
HEADLIGHTS	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	N/A
SEAT	High Back w/ seat springs	High Back w/ seat springs	High Back w/ seat springs	High Back w/ seat springs	Mid Back w/ seat springs	Mid Back w/ seat springs	Mid Back w/ seat springs	Mid Back w/ seat springs	Mid Back w/ seat springs	Mid Back w/ seat springs	Low Back w/ seat springs
HOUR METER	Standard	Standard	Standard	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
MACHINE DIMENSION											
WEIGHT (LBS)	645	630	615	525	540	540	525	520	515	515	425
LENGTH (INCHES)	69"	69"	69"	70"	70"	70"	70"	70"	70"	70"	64"
WIDTH (INCHES)	64"	58"	52"	44"	57"	57"	54"	44"	44"	44"	42"
HEIGHT (INCHES)	42"	42"	42"	40"	40"	40"	40"	40"	40"	40"	37"
ATTACHMENTS	Powered Bagger Kit, Mulching Kit, Sun Shade, Spreader, Dump Cart, Snow Blade (except ZT 1734XL), Snow Head (except ZT 1734XL), Roller, Aerator, Dethatcher, Sprayer, Trailer Hitch Kit, Head Light Kit, FlexTend™ Shoulder Support System					Powered Bagger Kit, Mulching Kit, Sun Shade, Spreader, Dump Cart, Roller, Aerator, Dethatcher, Sprayer, Head Light Kit, FlexTend™ Shoulder Support System, Wheel Covers, Hood Kit, Seat Armrest Kit					Mulching Kit, Trailer Hitch Kit, Spreader, Dump Cart, Roller, Aerator, Dethatcher, Non-Powered Bagger, Sprayer

PRODUCT NAME	WAW 1034	PRO 21 XD	Classic LM 21SW		Classic LM 21S		Classic LM 21	Blade Runner™ SPE	Blade Runner™ SP	Blade Runner™ P
MODEL NUMBER	911404	911253	911137	911264	911136	911262	911260	911226	911222	911220
WARRANTY	2 Year	2 Yr Consumer, 1 Yr Commercial	2 Year		2 Year		2 Year	2 Year	2 Year	2 Year
ENGINE	Briggs & Stratton® I/C	Kawasaki®	Kawasaki® FJ180V	Kohler® XT-7	Kawasaki® FJ180V	Kohler® XT-7	Kohler® XT-7	Kohler® XT-7	Kohler® XT-7	Kohler® XT-7
ENGINE RATING	10.5 hp	6 hp	6.0 hp	7 ft-lbs Net Torque	6.0 hp	7 ft-lbs Net Torque	7 ft-lbs Net Torque	7 ft-lbs Net Torque	7 ft-lbs Net Torque	7 ft-lbs Net Torque
DRIVE SYSTEM	Variable Speed Belt Drive	Variable Speed Belt Drive	Infi-Speed		Infi-Speed		Push	Variable Speed Belt Drive	Variable Speed Belt Drive	Variable Speed Belt Drive
FUEL CAPACITY GALLONS (LITERS)	0.75 gallon (2.83L)	0.53 gallon (2L)	0.37 gallon (1.4L)		0.37 gallon (1.4L)		0.37 gallon (1.4L)	0.37 gallon (1.4L)	0.37 gallon (1.4L)	0.37 gallon (1.4L)
GROUND SPEED (Appx. Mph) (Forward/Rev)	4 mph/2 mph	3.75	4 mph		4 mph		N/A	2.75 mph	2.75 mph	Push
STARTER	Electric	Recoil	Recoil		Recoil		Recoil	Recoil/E.S.	Recoil	Recoil
DECK										
DECK MATERIAL	14 ga	14 ga	14 ga		14 ga		14 ga	14 ga	14 ga	14 ga
DECK CONSTRUCTION	Stamped	Stamped	Stamped		Stamped		Stamped	Stamped	Stamped	Stamped
NUMBER OF SPINDLES	2	1	1		1		1	1	1	1
BLADE TIP SPEED (FPM)	17,500	17,500	18,000		18,000		18,000	18,000	18,000	18,000
SPINDLE MATERIAL	1215 Steel	Steel	Steel		Steel		Steel	Steel	Steel	Steel
SPINDLE SHAFT	1"	7/8"	7/8"		7/8"		7/8"	7/8"	7/8"	7/8"
SPINDLE BEARINGS	Sealed Ball	Sealed Ball	Sealed Ball		Sealed Ball		Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball
DECK DRIVE	Belt	Direct	Direct		Direct		Direct	Direct	Direct	Direct
DECK ENGAGEMENT	PTO Lever	N/A	N/A		N/A		N/A	N/A	N/A	N/A
DECK LIFT SYSTEM	Manual	Manual	Manual		Manual		Manual	Manual	Manual	Manual
CUTTING WIDTH	34"	21"	21"		21"		21"	21"	21"	21"
CUTTING HEIGHTS	1.5"-3.5"	1"-4"	1"-3.25"		1"-3.25"		1"-3.25"	1"-4"	1"-4"	1"-4"
CUTTING POSITIONS	6	13 (2 Zones)	6		6		6	7	7	7
WHEELS										
FRONT AXLE	Swivel	Yes	Swivel		Yes		Yes	No	No	No
FRONT	8	8.25	7.5		7.5		7.5	8.5	8.5	8.5
REAR	13	8.25	10.5		10.5		10.5	8.5	8.5	8.5
FEATURES										
SAFETY	ANSI Compliant	ANSI Compliant	ANSI Compliant		ANSI Compliant		ANSI Compliant	ANSI Compliant	ANSI Compliant	ANSI Compliant
HOOD	No	No	No		No		No	No	No	No
HEADLIGHTS	No	No	No		No		No	No	No	No
SEAT	No	No	No		No		No	No	No	No
HOUR METER	No	No	No		No		No	No	No	No
MACHINE DIMENSION										
WEIGHT (LBS)	275	125	104		121		100	92	92	78
LENGTH (INCHES)	67"	62.5"	61.5"		61.5"		61.5"	70"	70"	70"
WIDTH (INCHES)	44.5"	23.5"	23"		23"		23"	21.5"	21.5"	21.5"
HEIGHT (INCHES)	38"	40.6"	38"		38"		38"	47"	47"	47"
ACCESSORIES/ATTACHMENTS										
Mulching Kit, Bagger Kit, Discharge Cover		Rear Bagger Kit, Mulching Kit, Leaf Shredder Kit	Dethatcher, Rear Bagger Kit, Mulching Kit, Leaf Shredder Kit, Straight Axle Conversion Kit/Swivel Wheel Kit				Bagger Kit, Height of Cut Extension			

AN ARIENS COMPANY

© Registered trademark and TM trademark of Ariens Company. HP is a function of the engine manufacturer's rating. Mower features and specifications subject to change without notice. © 2009 Ariens Company